



DOWA®**DoUVLEDs****DOWA SUPERB UV LED SOLUTIONS****MODEL xFxVL-1H411 series****T018 Hemispherical Can Type****Mechanical Specifications and Materials (Unit: mm)****Product ID****265nm: DF7VL-1H411****280nm: DF8VL-1H411****310nm: UF1VL-1H411****325nm: UF3VL-1H411****340nm: UF4VL-1H411****Typical Optical-Electrical Characteristics (I_F=20mA, T_a=25°C)**

Item	Symbol	Unit	DF7VL	DF8VL	UF1VL	UF3VL	UF4VL
Peak Wavelength	λ_p	nm	265±5	280±10	310±5	325±5	340±5
Radiant Flux	P _o	mW	0.7	1.1	0.6	0.9	1.1
Full Width at Half Maximum	Δ	nm	13	12	15	11	9
Forward Voltage	V _F	V	8-9	6.5	6-7	4.5	4.0
Response*	rise time	t _r	ns	-	16	20	12
	fall time	t _f	ns	-	8	9	8
Viewing Half Angle	2θ _{1/2}	deg.	40	40	40	40	40

*Test condition : Frequency=100kHz, duty=1%, I_p=200mA**Absolute Maximum Ratings**

Item	Symbol	Unit	Ambient Temperature	
Forward Current	I _{Fmax}	mA	40	T _a =25°C
Operating Temperature	T _{OPR}	°C	-30 ~ +80	
Storage Temperature	T _{STG}	°C	-40 ~ +100	
Soldering Temperature	T _{SOL}	°C	350 (within 3sec)	Manual soldering process
			250 (within 5sec)	Flow soldering process





DoUVLEDs

DOWA SUPERB UV LED SOLUTIONS



Forward Voltage vs Forward Current

Forward Current vs Radiant Flux



Peak Wavelength vs Relative Intensity

Radiation Pattern



	WARNING
	<ul style="list-style-type: none"> • LEDs emit very strong UV radiation. • Don't look directly into the LED light. UV radiation can harm your eyes. • To prevent even inadequate exposure, wear protective eyewear. • If LEDs are embedded in devices, please indicate warning labels against the UV light LED used. • Keep out of reach of children. • Specification and dimension are subject to change for improvement without notice.

[Japan] DOWA Electronics Materials Co., Ltd
 Akihabara UDX Bldg. 4-14-1 Sotokanda, Chiyoda-ku, Tokyo 101-0021, Japan / Phone: +81-3-6847-1253

[USA] DOWA International Corp. San Jose office
 4320 Stevens Creek Blvd. Suite 125, San Jose CA 95129, USA / Phone: +1-408-236-7560

[EU] DOWA HD Europe GmbH
 Ostendstrasse 196, D-90482, Nurnberg, Germany / Phone: +49-911-56989-320

